

# TRACTOR SPECIFICATIONS

Model	LX2610SUHSD	LX2610HSD	LX3310HSD	LX2610HSDCC	LX3310HSDCC
<b>Engine</b>					
Type	E-TVCS, liquid cooled, 3-cylinder diesel		E-CDIS, liquid cooled, 4-cylinder diesel	E-TVCS, liquid cooled, 3-cylinder diesel	E-CDIS, liquid cooled, 4-cylinder diesel
Make, Model	D1305-E4-D36-R		V1505-CR-TE5-D36R1	D1305-E4-D26-Q	V1505-CR-TE5-D36Q1
PTO horsepower	HP (kW)	19.5 (14.5)	27.0 (20.1)	19.5 (14.5)	27.0 (20.1)
Engine gross horsepower*	HP (kW)	24.8 (18.5)	30.8 (23.0)	24.8 (18.5)	30.8 (23.0)
Rated RPM	rpm	2500			
Bore and stroke	in. (mm)	ø3.1 × 3.5 (ø78 × 88)	ø3.1 × 3.1 (ø78 × 78.4)	ø3.1 × 3.5 (ø78 × 88)	ø3.1 × 3.1 (ø78 × 78.4)
Displacement	cu. in. (cc)	77.0 (1261)	91.5 (1498)	77.0 (1261)	91.5 (1498)
Air cleaner		4.5 inch Dual paper element	6.0 inch Dual paper element	4.5 inch Dual paper element	6.0 inch Dual paper element
Lubrication		Forced lubrication			
Cooling system		Pressurized radiator			
Radiator fan		Radial air flow			
<b>Capacities</b>					
Fuel tank	gal (ℓ)	7.1 (27.0)		8.4 (32)	
Cooling system	qts. (ℓ)	4.5 (4.3)			
Engine oil	qts. (ℓ)	4.2 (4.0)	5.0 (4.7)	4.2 (4.0)	5.0 (4.7)
Transmission case	gal (ℓ)	4.0 (15)			
<b>Drive train</b>					
Clutch		N / A			
Transmission		HST (3 ranges)			
Differential lock		Standard			
Final drive		Spur gear			
Brake		Multi-plate wet disc			
<b>PTO</b>					
Type		Independent			
Rear	rpm	540			
Mid	rpm	N/A	2500		
<b>Hydraulics</b>					
Type		Open center			
Pump		Dual pump			
Total pump output	gpm (ℓ/min.)	8.7 (33.1)			
Hydraulic outlet		Rear outlet			
3-point hitch		Category I			
Hydraulic control system		Position control valve			
Lift capacity at lift point	lbs. (kg)	2139 (970)			
24" behind LPlbs. (kg)		1676 (760)			
Steering		Hydraulic power steering			
<b>Standard tire size</b>					
Front	R1	7-12			
	R4	23 × 8.50-14 / 25 × 8.50-14		23 × 8.50-14	
	R14	23 × 8.50-12 / 25 × 8.50-14		23 × 8.50-12	
Rear	R1	12.4-16			
	R4	12.4-16 / 15-19.5		12.4-16	
	R14	14-17.5 / 15-19.5		14-17.5	
<b>Traveling speeds (at rated engine rpm)</b>					
Forward (R1)	mph (km/h)	0-11.2 (0-18.0)	0-13.6 (0-21.9)	0-11.2 (0-18.0)	0-13.6 (0-21.9)
Reverse (R1)	mph (km/h)	0-8.4 (0-13.5)	0-10.3 (0-16.5)	0-8.4 (0-13.5)	0-10.3 (0-16.5)
<b>Dimensions (w/ R1 tires)</b>					
Overall length (w/o 3P)	in. (mm)	101.8 (2585)		103.9 (2640)	
Overall width (min. tread)	in. (mm)	53.7 (1365)			
Overall height	in. (mm)	88.4 (2245)			
Wheelbase	in. (mm)	65.6 (1666)			
Ground clearance	in. (mm)	14.6 (370)			
Turning radius with brake	feet (m)	6.9 (2.1)			
Weight	lbs. (kg)	1830 (830)	2072 (940)	2293 (1040)	2557 (1160)
<b>Other Features</b>					
Open Station (SU) models		Lower link stabilizer, Drawbar, Tool box, 12V power socket			
Open Station models		Cruise control (Multi-stage notch), Tilt-steering, Deluxe seat with arm rest, Parallel link with damper seat suspension, Lower link stabilizer, Drawbar, Tool box, 12V power socket			
CAB models		4-pillar integrated cabin, Cruise control (Multi-stage notch), Tilt-steering, Deluxe seat with arm rest, Parallel link seat suspension, Telescopic lower links, Lower link stabilizer, Drawbar, Front and Rear LED Work Lights, Tool box, Cabin Interior Light, Speakers, 12V power socket, Front & Rear wiper with washer, Rear defogger, Rear hatch half lock			

\*SAE J1995  
Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

# IMPLEMENT SPECIFICATIONS

## Front Loader Specifications

Model	LA535	
Maximum lift height (to bucket pivot pin)	in. (mm)	84 (2134)
Clearance with attachment dump	in. (mm)	66.8 (1696)
Maximum dump angle	deg.	36
Max. rollback angle	deg.	30
Lift capacity (pivot pin)	lbs. (kg)	1067 (484)*
Lift capacity (19.7 in. forward)	lbs. (kg)	769 (349)*
Breakout force (pivot pin)	lbs. (kg)	2245 (1019)
Breakout force (19.7 in. forward)	lbs. (kg)	1634 (742)
Net weight (approx.)	lbs. (kg)	562 (255)

\* With 2-lever quick coupler

## Backhoe Specifications

Model	BH77	
Transport height	in. (mm)	80.7 (2051)
Stabilizer spread - transport	in. (mm)	51.8 (1315)
Ground clearance	in. (mm)	12.6 (319)
Digging depth 2ft flat bottom	in. (mm)	91.8 (2331)
Operating height fully raised	in. (mm)	119.2 (3029)
Loading height (length of dipper cyl. = 715 mm)	in. (mm)	66.7 (1693)
Loading reach (length of dipper cyl. = 715 mm)	in. (mm)	50.8 (1290)
Reach from swing pivot	in. (mm)	124.6 (3165)
Swing pivot to rear axle center line	in. (mm)	38.4 (976)
Angle of departure per SAE J1234	deg.	17.3
Swing arc	deg.	180
Net weight (approx.)	lbs. (kg)	1105 (501)*

\* Including backhoe sub frame weight (Open Station)

## Mid Mount Mower Specifications

Models	RCK60-30BB	RCK72-30BB
Type	Side Discharge	
Number of blades	3	
Mounting method	Floating	
Cutting width	in. (mm)	60 (1524) / 72 (1826)
Cutting height	in. (mm)	1.5 to 4.0 (38 to 102)
Adjustment of cutting height	Gauge wheel	
Net weight (approx.)	lbs. (kg)	374 (170) / 463 (210)